

**YÜK MAKARASI / PULLEY BLOCKS****NL-HPB 10****NL-HPB 20****NL-HPB 32****NL-HPB 64**

		<b>1000</b>	<b>2000</b>	<b>3200</b>	<b>6400</b>	
<b>Çalışma yükü / Working load</b>						kg
<b>Mandal açıklığı / Hook hatch</b>		<b>23</b>	<b>27</b>	<b>31</b>	<b>42</b>	mm
<b>Halat ölçüsü / Rope diameter</b>		<b>Ø7</b>	<b>Ø13</b>	<b>Ø15</b>	<b>Ø18</b>	mm
<b>Ölçüler / Dimensions</b>	B	<b>118</b>	<b>199</b>	<b>230</b>	<b>270</b>	mm
	B <sub>1</sub>	<b>76</b>	<b>92</b>	<b>108</b>	<b>116</b>	mm
	B <sub>2</sub>	<b>17</b>	<b>24</b>	<b>28</b>	<b>35</b>	mm
	C	<b>23</b>	<b>27</b>	<b>31</b>	<b>42</b>	mm
	D <sub>1</sub>	<b>85</b>	<b>150</b>	<b>180</b>	<b>210</b>	mm
	D <sub>2</sub>	<b>105</b>	<b>190</b>	<b>220</b>	<b>260</b>	mm
	L	<b>305</b>	<b>425</b>	<b>496</b>	<b>655</b>	mm
	L <sub>1</sub>	<b>200</b>	<b>263</b>	<b>295</b>	<b>375</b>	mm
	L <sub>2</sub>	<b>23</b>	<b>30</b>	<b>40</b>	<b>47</b>	mm
	R	<b>4</b>	<b>7</b>	<b>9</b>	<b>10</b>	mm
<b>Ağırlık / Weight</b>		<b>3.3</b>	<b>8.9</b>	<b>15.5</b>	<b>26.5</b>	kg

- Netlift yük makaralarının bir yüzü halatın bobine rahat yerleştirilebilmesi için açılabilir.
- Kancanın çekim yönüne hareketi kasnak bloğunu güvenli bir şekilde kilitleyebilir.
- Yüksek kaliteli çelikten imal edilmiş bobinlerin yivleri özel makinalarda açılmıştır.
- prEN13157:2003 ve Machinery Directive 2006/ 42 EC'ye göre imal edilmiştir.

- One side of the NETLIFT pulley blocks is hinged and can be opened for easy and quick positioning of the rope on the sheave.
- Swinging the hook in the direction of pull securely locks the pulley block.
- The high quality cast steel sheaves have machined grooves
- Manufactured according to prEN 13157:2003, machinery directive 2006/ 42 EC

Art.No. 52000079

**NL-HPB 10**

Art.No. 52000080

**NL-HPB 20**

Art.No. 52000081

**NL-HPB 32**

Art.No. 52000082

**NL-HPB 64**